

Pigment Red 179 S-0610 for Coatings

High Performance Perylene Pigments Producer in China

Pigment Red 179 (S-0610) is a high performance perylene pigments, which is widely used in automobile varnish and refinishing paint, plastics, inks and other industrial paint. it has strong light fastness and heat resistance, and the color strength is also very high.

nicals Product		Partical Size					
Trade Name	Pigment Red 179	D(v, 0. 5) : 25. 4	43 µm D[4,	3]: 41.77 μm	D[3,2]: 11.	99 µm	
C.I. No.	C.I.71130	SSA: 0.18 m		cle RI: 2.520+0.100			
CAS No.	5521-31-3	100. 0				6.3	
EC No.	226-866-1	80. 0				5.6	
Aolecular Formula	$C_{26}H_{24}N_2O_4$	60.0 100 100 100 100 100 100 100				4.2 3.5 2.8	
sical Data		30. 0 20. 0 10. 0			\sim	2.1 1.4 0.7	
Physical State	Powder	0.0	1.0	10.0 Size(µm)	100.0	0.0	
Appearance	Amaranthine powder		BET Surface Area				
Oil absorption	45						
Molecular Weight	418.42	序号 2 3	Pd 12.54606 16.16254		P/Po 0.06278 0.09920	V 6.84472 7.47412	
PH Value	5-7	4 5 6	19.81961 23.47668 27.10939	17.61563	0.13562 0.17180 0.20774	7.95185 8.39854 8.81420	
Light Fastness	7-8	7 8	31.29412 35.17848	25.18141	0.20774 0.24558 0.28342	9.24666 9.68711	
Heat Resistance	200°C	9	39.05473	32.94203	0.32127	10.11957	
Strength %	100 ± 5	斜率	截距	Vm		0	
Moisture %	≪0.5	0.14375	0.00017	6.94854	848.6	67382	
Density	54.46g/100ml		比	表面积(m2/g): 30.2	9563		
llatory Compliance		ARCD					
HS FDA Phthalate	AP(89)1 SVHC	١-	ΔE*, D65/10° +Δb*		ΔE	E*, D65/10° +Δb*	
lications		0.5		1-0.5			
utomobile Varnish	•	0		+0a* ; 0- 0	- 0a -	•	
Refinishing Paint	•	0.5	1032	-0.5		1.0 ³	
Pringting Ink	0	.1	-Δb*			-4b*	
Plastic	0	-1 -0.5	0 0.5	1	-1 -0.5	0 0	
• recommended	O limited suitability						

鸿港化工

Liaoning HongGang Chemicals Co., Ltd No.6, Wanhe 2 Road, Aromatics Base, Liaoyang City, Liaoning Prov, China <u>Tel:0419-7675988</u> Fax:0419-7675289 E-mail: Lyns3322@163.com Sales@liangangchem.com

www.liangangchem.com